
SCSI DB 100 Pin Male Connector With Screw



Product Details

Starte IDC Type SCSI DB 100 pin male Connector with screw and metal Hood, this scsi DB 100 pin IDC connector pin arrangement in two rows, one on top of the other. The top row has 50 pins and the lower row has 50 pins. Often used on the cable for PCI Card.

Product Parameters of DB 100 pin male Connector with Screw:

Item	SCSI DB100 pin male connector with screw
Brand	Starte
Product type	SCSI cable and connector
No. Of Contact	100 pin
Contact Type	1.27mm cable receptacles Connector IDC type
Options	Male, Screw,Assembly
Wire	28AWG or 30AWG support
Contact Finishes	Gold Selective Plating
MOQ	1 PCS
Sample	Free
Package	Bags
Warranty	Two years

Technical Parameters of SCSI HD 100 pin male Connector:

Connector Material	
Housing	Plastic Thermoplastic P.B.T UL94V-0, Black
Contacts	Copper Alloy Gold Selective Plated
Front Shell	Steel, Nickel Plated Over Copper
Cover&Holder	Plastic Thermoplastic P.B.T UL94V-0, Black
Straight exit Metal cover Material	
Back Shell	Zinc Alloy, Nickel Plated Over Copper
Flat Screws	Steel, Nickel Plated Over Copper
Jack screws	Steel, Nickel Plated Over Copper
Cable Clipper	Steel, Nickel Plated Over Copper
Electrical Characteristics	
Contact Current Rating	1.0 Amp
Dielectric Withstanding Voltage	500V AC
Insulation Resistance	500MΩ/ Min
Contact Resistance	35mΩ /Max
Operation Temperature	-55°C~+105°C

Application of HD 100 pin male scsi connector:

- 1)motion controller, serial PCIx card
- 2)data acquisition control system breakout board
- 3)RAIDs,CD ROM,File Server
- 4) DIN-Mount Screw Terminal Panel