



National
Semiconductor
Corporation

DM74AS157/DM74AS158

Quad 1 of 2 Line Data Selectors/Multiplexers

General Description


These data selectors/multiplexers contain inverters and drivers to supply full on-chip data selection to the four output gates. A separate strobe input is provided. A 4-bit word is selected from one of two sources and is routed to the four outputs. The AS157 presents true data whereas the AS158 presents inverted data to minimize propagation delay time.

Features

- Switching specifications at 50 pF
- Switching specifications guaranteed over full temperature and V_{CC} range

- Advanced oxide-isolated, ion-implanted Schottky TTL process
- Functionally and pin for pin compatible with Schottky, low power Schottky, and advanced low power Schottky TTL counterpart
- Improved AC performance over Schottky, low power Schottky, and advanced low power Schottky counterparts
- Expand any data input point
- Multiplex dual data buses
- General four functions of two variables (one variable is common)
- Source programmable counters

Connection Diagram



Function Table

Inputs				Output Y	
Strobe	Select	A	B	AS157	AS158
H	X	X	X	L	H
L	L	L	X	L	H
L	L	H	X	H	L
L	H	X	L	L	H
L	H	X	H	H	L

H = High Level, L = Low Level, X = Don't Care

*Contact your local NSC representative about surface mount (M) package availability.

Absolute Maximum Ratings

If Military/Aerospace specified devices are required, contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Supply Voltage	7V
Input Voltage	7V
Operating Free Air Temperature Range	0°C to +70°C
Storage Temperature Range	-65°C to +150°C

Note: The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the "Electrical Characteristics" table are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

Recommended Operating Conditions

Symbol	Parameter	DM74AS157, 158			Units
		Min	Nom	Max	
V _{CC}	Supply Voltage	4.5	5	5.5	V
V _{IH}	High Level Input Voltage	2			V
V _{IL}	Low Level Input Voltage			0.8	V
I _{OH}	High Level Output Current			-2	mA
I _{OL}	Low Level Output Current			20	mA
T _A	Free Air Operating Temperature	0		70	°C

Electrical Characteristics

over recommended operating free air temperature range. All typical values are measured at V_{CC} = 5V, T_A = 25°C.

Symbol	Parameter	Conditions		Min	Typ	Max	Units
V _{IK}	Input Clamp Voltage	V _{CC} = 4.5V, I _I = -18 mA				-1.2	V
V _{OH}	High Level Output Voltage	V _{CC} = 4.5V to 5.5V, I _{OH} = -2 mA		V _{CC} - 2			V
V _{OL}	Low Level Output Voltage	V _{CC} = 4.5V, I _{OL} = 20 mA			0.35	0.5	V
I _I	Input Current at Max Input Voltage	V _{CC} = 5.5V, V _{IH} = 7V		Select		0.2	mA
				All Others		0.1	
I _{IH}	High Level Input Current	V _{CC} = 5.5V, V _{IH} = 2.7V		Select		40	μA
				All Others		20	
I _{IL}	Low Level Input Current	V _{CC} = 5.5V, V _{IL} = 0.4V		Select		-1	mA
				All Others		-0.5	
I _O	Output Drive Current	V _{CC} = 5.5V, V _O = 2.25V		-30		-112	mA
I _{CC}	Supply Current	V _{CC} = 5.5V		'AS157		17.5	mA
				'AS158		15.6	22.5 mA


'AS157 Switching Characteristics over recommended operating free air temperature range (Note 1)

Symbol	Parameter	Conditions	From (Input)	To (Output)	DM74AS157		Units
					Min	Max	
t _{PLH}	Propagation Delay Time, Low to High Level Output	V _{CC} = 4.5V to 5.5V, C _L = 50 pF, R _L = 500Ω	Data	Y	1	6	ns
t _{PHL}	Propagation Delay Time, High to Low Level Output		Data	Y	1	5.5	ns
t _{PLH}	Propagation Delay Time, Low to High Level Output		Strobe	Y	2	10.5	ns
t _{PHL}	Propagation Delay Time, High to Low Level Output		Strobe	Y	2	7.5	ns
t _{PLH}	Propagation Delay Time, Low to High Level Output		Select	Y	2	11	ns
t _{PHL}	Propagation Delay Time, High to Low Level Output		Select	· Y	2	10	ns


'AS158 Switching Characteristics over recommended operating free air temperature range (Note 1)

Symbol	Parameter	Conditions	From (Input)	To (Output)	DM74AS158		Units
					Min	Max	
t _{PLH}	Propagation Delay Time, Low to High Level Output	V _{CC} = 4.5V to 5.5V, C _L = 50 pF, R _L = 500Ω	Data	Y	1	5	ns
t _{PHL}	Propagation Delay Time, High to Low Level Output		Data	Y	1	4.5	ns
t _{PLH}	Propagation Delay Time, Low to High Level Output		Strobe	Y	2	6.5	ns
t _{PHL}	Propagation Delay Time, High to Low Level Output		Strobe	Y	2	10	ns
t _{PLH}	Propagation Delay Time, Low to High Level Output		Select	Y	2	9.5	ns
t _{PHL}	Propagation Delay Time, High to Low Level Output		Select	Y	2	10.5	ns

Note 1: See Section 1 for test waveforms and output load.

Logic Diagrams

TL/F/6290-2



TL/F/6290-3