


# ATS640LSB

## TRUE ZERO-SPEED, SELF-CALIBRATING, DIFFERENTIAL HALL-EFFECT GEAR-TOOTH SENSOR FOR TWO-WIRE APPLICATIONS



Pin 1 = Supply  
Pin 2 = Current Output  
Pin 3 = Internal Connection  
Pin 4 = Ground

Dwg. AH-006-3

### ABSOLUTE MAXIMUM RATINGS at $T_A = 25^\circ\text{C}$

Supply Voltage, $V_{CC}$ .....	26.5 V*
Reverse Supply Voltage, $V_{RCC}$ .....	-24 V
Output OFF Voltage, $V_{OUT}$ .....	26.5 V
Reverse Output Current, $I_{ROUT}$ .....	50 mA
Package Power Dissipation, $P_D$ .....	See Graph
Operating Temperature Range, $T_A$ .....	-40°C to +150°C*
Storage Temperature, $T_S$ .....	+170°C

\* Operation at increased supply voltages with external circuitry is described in Applications Information. Devices for operation at increased temperatures are available on special order.

The ATS640LSB Hall-effect gear-tooth sensor is a peak detecting device that uses internal gain control to provide extremely stable duty cycles down to zero speed. Each sensor subassembly consists of a high-temperature plastic shell that holds together a samarium-cobalt magnet, a pole piece, and a true zero-speed BiCMOS differential Hall-effect gear-tooth sensor IC that has been optimized to the magnetic circuit. This small package can be easily assembled and used in conjunction with a wide variety of gear shapes and sizes.

The gear-sensing technology used for this sensor subassembly is Hall-effect based. The sensor incorporates a dual-element Hall IC that switches in response to differential magnetic signals created by a ferrous target. The sophisticated self-calibrating digital-processing circuitry normalizes the internal gain of the device to minimize the effect of air gap variations, and to reduce vibration sensitivity. The circuit eliminates magnet and system offsets such as those caused by tilt yet provides zero-speed detection capabilities without the associated running jitter inherent in classical digital solutions.

This sensor system is ideal for use in gathering speed, position, and timing information using gear-tooth-based configurations. The ATS640LSB is particularly suited to those applications that require extremely accurate duty cycle control or accurate edge detection such as in ABS applications. The lower vibration sensitivity also makes this device extremely useful for transmission speed sensing.

continued next page...

*Some restrictions may apply to sales for automotive applications.  
Contact factory for details.*

Always order by complete part number: **ATS640LSB**.


# ATS640LSB

## TRUE ZERO-SPEED, TWO-WIRE GEAR-TOOTH SENSOR

### FEATURES AND BENEFITS

- Internal Current Regulator for 2-Wire Operation
- True Zero-Speed Operation
- Self Calibrating
- Extremely Stable Duty Cycle with Temperature
- Fully Optimized Differential Digital Gear-Tooth Sensor
- Large Operating Air Gaps
- Air-Gap Independent Switch Points
- High Vibration Immunity
- Single-Chip Sensing IC for High Reliability
- Digital Output Representing Target Profile
- Small Mechanical Size
- Optimized Magnetic Circuit
- <math><200 \mu\text{s}</math> Typical Power-On Time
- AGC and Reference-Adjust Circuit
- Under-Voltage Lockout
- Wide Operating Voltage Range
- Defined Power-On State

### TYPICAL APPLICATION



### FUNCTIONAL BLOCK DIAGRAM

