

AG Series Dual-channel Arbitrary Waveform Generator

Accessories

The accessories subject to final delivery.



Power Cord



CD-Rom



Manual



09



USB

DDS



Main Feature

- + Advanced DDS technology, max 60MHz frequency output
- + Up to 250MS/s sample rate, and 1μHz frequency resolution
- + Vertical Resolution : 14 bits, up to 1M arb waveform length
- + Comprehensive waveform output : 5 basic waveforms, and 48 built-in arbitrary waveforms
- + Comprehensive modulation functions : AM, FM, PM, FSK, PWM, Sweep, and Burst
- + High-accuracy frequency counter integrated, supported range 100mHz - 200MHz
- + Supported SCPI
- + 4 inch high resolution (480 × 320 pixels) TFT LCD display

LILLIPUT[®]

E-mail : info@owon.com.hk

WWW.OWON.COM.HK

Fujian Lilliput Optoelectronics Technology Co., Ltd.

The Mansion of Optoelectronics, Hengsan Road
Lantian Industrial Zone, Zhangzhou 363005 China

Tel : +86.596.213.0430 Fax : +86.596.210.9272

Xiamen Lilliput Technology Co., Ltd.

5/F, B Area, Chuangxin Plaza, Software Park
Huandao Road, Xiamen 361005 China

Tel : +86.592.257.5666 Fax : +86.592.257.5669

Performance Specifications

Model	AG1012	AG1012F	AG1022	AG1022F	AG2052F ^{NEW!}	AG2062F ^{NEW!}
Channel	dual					
Frequency Output	10MHz	25MHz		50MHz	60MHz	
Sample Rate	125MS/s			250MS/s		
Vertical Resolution	14 bits					
Waveform						
Standard Waveform	Sine, Square, Pulse, Ramp, and Noise					
Arbitrary Waveform	Exponential Rise, Exponential Fall, Sin(x)/x, Step Wave, and others, total 48 built-in waveforms, and user-defined arbitrary waveform					
Frequency (resolution 1μHz)						
Sine	1μHz - 10MHz	1μHz - 25MHz		1μHz - 50MHz	1μHz - 60MHz	
Square	1μHz - 5MHz			1μHz - 25MHz	1μHz - 30MHz	
Pulse	1μHz - 5MHz			1μHz - 10MHz		
Ramp	1μHz - 1MHz					
Noise	25MHz (-3dB) (typical)					
Arbitrary Waveform	1μHz - 10MHz					
Amplitude						
Amplitude	1m Vpp - 10 Vpp (50Ω), 1m Vpp - 20 Vpp (high impedance)					
Resolution	1m Vpp or 14 bits					
DC Offset Range (AD+DC)	±5V (50Ω), ±10V (high impedance)					
DC Offset Range Resolution	1mV					
Load Impedance	50Ω (typical)					
Model	AG1012	Ag1022	AG1012F	AG1022F	AG2052F ^{NEW!}	AG2062F ^{NEW!}
Arbitrary Waveform						
Wave Length	2 pts to 8K pts				2 pts to 1M pts	
Sample Rate	125MS/s				250MS/s	
Vertical Resolution	14 bits					
Non-volatile Memory	26 waveforms					
Modulation						
Modulation Waveform	/	AM, FM, PM, FSK, Sweep, and Burst			AM, FM, PM, FSK, PWM, Sweep, and Burst	
Modulation Frequency	/	2mHz to 20.00KHz (FSK 1μHz - 100KHz)				
Counter						
Function	/	Frequency Period, +Width, -Width, +Duty, and -Duty				
Frequency Range	/	100mHz - 200MHz				
Frequency Resolution	/	6 digits				
Input / Output						
Display	4 inch (480 × 320 pixels) TFT LCD					
Type	external reference clock input / output	counter external modulation input / output, external trigger input / output, external reference clock input / output				
Communication Interface	USB host, USB device, RS232					
Mechanical						
Dimension (W×H×D)	235 × 110 × 295 (mm)					
Weight (without package)	3.00 kg					

Specifications subject to change without prior notice.