

5x20mm Fast-Acting Glass Fuse



Product Details

Overview

Quick Details

Place of Origin: Guangdong, China (Mainland)

Usage: Low Voltage

Breaking Capacity: High

Safety Standards: UL CSA VDE CCC

Fuse type: glass fuse

Tube material: Glass

Current rating : 0.1A 0.5A 1A 2A 3A 5A 10A 15A 20A 30A 40A

Size: 5.2x20

Voltage : 250V AC/DC

Conductor: copper

Colors: White, clear etc

Operating Temperature: -55C ~ 125C

Description:

Glass fuse : 5.2x20

Standard Package: 1,000

Category: Circuit Protection

Family: Fuses

Fuse Type: Cartridge, Glass
 Current Rating: 100mA ~ 20A
 Voltage Rating - AC: 250V
 Voltage Rating - DC: 250V
 Response Time: Fast
 Package / Case: 5mm x 20mm
 Mounting Type: Holder
 Breaking Capacity @ Rated Voltage: 50A
 Melting I²t: 95
 Approvals: CE, CSA, IMQ, SEMKO, UL, VDE
 Operating Temperature: -55°C ~ 125°C
 Size / Dimension: 0.201" Dia x 0.787" L (5.10mm x 20.00mm)
 Packaging: Bulk
 DC Cold Resistance: 0.011 Ohm

Fuse Type	Current Rating	Voltage Rating-AC/DC	Package / Case	RoHS
Cartridge, Glass	1A	250V	5mm x 20mm	RoHS
Cartridge, Glass	2.5A	250V	5mm x 20mm	RoHS
Cartridge, Glass	250mA	250V	5mm x 20mm	RoHS
Cartridge, Glass	3A	250V	5mm x 20mm	RoHS
Cartridge, Glass	500mA	250V	5mm x 20mm	RoHS
Cartridge, Glass	5A	250V	5mm x 20mm	RoHS
Cartridge, Glass	4A	250V	5mm x 20mm	RoHS
Cartridge, Glass	2A	250V	5mm x 20mm	RoHS
Cartridge, Glass	3.5A	250V	5mm x 20mm	RoHS
Cartridge, Glass	600mA	250V	5mm x 20mm	RoHS
Cartridge, Glass	375mA	250V	5mm x 20mm	RoHS
Cartridge, Glass	800mA	250V	5mm x 20mm	RoHS
Cartridge, Glass	100mA	250V	5mm x 20mm	RoHS
Cartridge, Glass	7A	250V	5mm x 20mm	RoHS
Cartridge, Glass	750mA	250V	5mm x 20mm	RoHS
Cartridge, Glass	1.6A	250V	5mm x 20mm	RoHS
Cartridge, Glass	6.3A	250V	5mm x 20mm	RoHS
Cartridge, Glass	6A	250V	5mm x 20mm	RoHS
Cartridge, Glass	8 A	250V	5mm x 20mm	RoHS
Cartridge, Glass	10A	250V	5mm x 20mm	RoHS
Cartridge, Glass	15A	250V	5mm x 20mm	RoHS
Cartridge, Glass	20A	250V	5mm x 20mm	RoHS

Features

- Halogen Free

Applications:

- Power Supplies
- Battery charger
- Monitor
- Adapter

Specifications

- Breaking Capacity @ Rated Voltage:35A ~ 10000A
- Current Rating:100mA ~ 20A
- DC Cold Resistance:0.013 Ohm ~ 11.9 Ohm
- Fuse Type:Cartridge, Glass
- Melting I²t:0.02 ~ 750
- Mounting Type:Holder
- Operating Temperature:-55°C ~ 125°C
- Package / Case:5mm x 20mm
- Packaging:Bulk
- Response Time:Medium
- Size / Dimension:0.201" Dia x 0.787" L (5.10mm x 20.00mm)
- Voltage Rating - AC:125V ~ 250V

Features:

1. We are certificated by ISO9001 UL DVE REACH.
2. Assembled according to customers' specifications.
3. Technology process: cutting , crimping, welding, assembly and testing.
4. Buyer's specifications are accepted.
5. 100%tested before shipment.
6. Stable quality, high reliability.