

WH-AA2R90-00E8P5 10E82G 10E84G WH-AA3R90-00E825 10E829



Brands: other

Model number: WH-AA3

Type: Sublimation

Interface type: Parallel port serial port

Maximum print format: None

Network printing: Network printing is not supported

Support for automatic duplex printing: No

Paper feeding method: Automatic

Energy efficiency rating: None

Version type: Hong Kong, Macao and Taiwan

Types of consumables: None

Specification

printing method : Direct thermal line printing

Out of paper detection : stand by

Loading method : Easy loading paper

Paper width : 57 mm

Print width : 48 mm

Resolution : 8 dots / mm (384 dots / line)

Print head life : 6,000,000 character lines

printing speed : 30mm / s (When the character rate is 25%.)

Character size : 6x8dots, 8x16dots, or12x24dots

Chinese Character Library : GB2312, 16x16dots, or24x24dots

Dimensions (WxHxD mm) : 83mmx58.5mmx47.5mm

Installation size (WxH mm) : 78mmx53.5mm

Embedding depth : 45mm

Specifications of paper : Thermal roll paper (57mm wide, 30mmø)

Interface : Serial RS-232C / 485 / (Serial TTL & Parallel)

Input power : DC 5V, 3A

Operating temperature : 5 ° C ~ 50 ° C

storage temperature : -20 ° C ~ 60 ° C

Operating humidity : 10% ~ 80%

Storage humidity : 10% ~ 90%