



SPECIFICATIONS
 Current Rating: 0.5 Amp
 Dielectric Withstanding Voltage: 500V AC Min.
 Contact Resistance: 30 Milliohms Max.
 Insulation Resistance: 1000 Megohms Min.
 Temperature Range: -55°C To +85°C
 Insulator: Glass-Reinforced Thermoplastic
 Contact: Copper Alloy, Tin Plated

Pin	A	B	C	Pin	A	B	C
02	1.00	3.1	5	20	19.00	21.1	23
03	2.00	4.1	6	21	20.00	22.1	24
04	3.00	5.1	7	22	21.00	23.1	25
05	4.00	6.1	8	23	22.00	24.1	26
06	5.00	7.1	9	24	23.00	25.1	27
07	6.00	8.1	10	25	24.00	26.1	28
08	7.00	9.1	11	26	25.00	27.1	29
09	8.00	10.1	12	27	26.00	28.1	30
10	9.00	11.1	13	28	27.00	29.1	31
11	10.00	12.1	14	29	28.00	30.1	32
12	11.00	13.1	15	30	29.00	31.1	33
13	12.00	14.1	16	31	30.00	32.1	34
14	13.00	15.1	17	32	31.00	33.1	35
15	14.00	16.1	18	33	32.00	34.1	36
16	15.00	17.1	19	34	33.00	35.1	37
17	16.00	18.1	20	35	34.00	36.1	38
18	17.00	19.1	21	36	35.00	37.1	39
19	18.00	20.1	22				

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. 12969
 APPROVED BY MEI
 CHECKED BY BECKY
 DRAWING BY HZF
 SCALE NONE
 REV. BO
 UNIT mm
 UNLESS OTHERWISE SPECIFIED TOLERANCES ARE:
 X. ±0.40
 .X ±0.30
 .XX ±0.20
 .XXX ±0.10

BO	NEW RELEASE	BECKY	02/10/2006
NO. REV.	REVISIONS	CHK	DATE