

KCD1-116B/2P



RoHS

跷板开关系列

ROCKER SWITCHES SERIES

YUEQING JINGHAN ELECTRONICS CO., LTD.




KCD1-116B/2P



KCD1-116B/3P



KCD1-116B/3PL



面板开孔 Panel Opening	面板厚度 Panel thickness	X ^{+0.10}	Y ^{+0.10}
0.6-1.2		19	19
1.3-2		19.2	
2-3		19.4	

项目 Item	参数 Parameter
额定电压、电压 Rated voltage	6A 250V AC
额定电流 Rated current	10A 125V AC 10(B)A 250V AC
绝缘电阻 Insulated resistance	≥ 100M Ω
接触电阻 Contact resistance	≤ 50m Ω
介电强度(板间) Dielectric strength	1500VAC/5S
电寿命 Endurance	≥ 10000 Cycles
使用温度 Ambient temperature	T 85

系列号 Series No	电路图 Circuit diagram	端子规格 Terminal	开关标记 Making	颜色代码 Color code
KCD1-116B/2P	ON-OFF 	A 	1 空白 No Making	K
KCD1-116B/3P	ON-ON 	B 	2 ○ —	W
		T 	3 ●	Y
		L 	4 米 米	R
			5 ○	G
			6 ○	O
			7 客人要求	B

The Main Technical Parameters

Item	Mini ON OFF Rocker Switch
Mterial	PA66 /PC
Rating	10A 125VAC/6A 250VAC
Contact Resistance	≤50MΩ
Insulation Resistance	≥500VDC100mΩ
OperatingTemperature	-25C~+85C
Ambient Temperature	-10°C~+85 °C
Dielectric Strength	1500VAC,1 Minute
Type	ROCKER SWITCH
Elactic life	>10000 Cycles
Electrical Life	>50000 Cycles
Terminals & Mid pins	Copper with silver plated
Contacts	Copper with compound silver
Terminals & Mid pins	Copper with silver plated