

SERIES 15830, SERIES 15930 DTL INTEGRATED CIRCUITS

DTL SMALL-SCALE INTEGRATION (SSI)

| Function | Operating Temperature | | Packages* | |
|--|-----------------------|-------------|-----------|------|
| | Ranges | | Dual-In- | |
| | -55°C to 125°C | 0°C to 75°C | Line | Flat |
| GATES WITH 6-kΩ PULL-UP RESISTORS | | | | |
| Expandable Dual 4-Input NAND Gates | SN 15930 | SN 15830 | J | N U |
| Quadruple 2-Input NAND Gates | SN 15946 | SN 15846 | J | N U |
| Triple 3-Input NAND Gates | SN 15962 | SN 15862 | J | N U |
| Dual 5-Input NAND Gates | SN 151900 | SN 151800 | J | N U |
| Expandable 8-Input NAND Gates | SN 151902 | SN 151802 | J | N U |
| 10-Input NAND Gates | SN 151904 | SN 151804 | J | N U |
| Quadruple 2-Input AND Gates | SN 151906 | SN 151806 | J | N U |
| Quadruple 2-Input OR Gates | SN 151908 | SN 151808 | J | N U |
| Quadruple 2-Input NOR Gates | SN 151910 | SN 151810 | J | N U |
| Quadruple 2-Input Exclusive-OR Gates | SN 151912 | SN 151812 | J | N U |
| GATES WITH 2-kΩ PULL-UP RESISTORS | | | | |
| Quadruple 2-Input NAND Gates | SN 15949 | SN 15849 | J | N U |
| Expandable Dual 4-Input NAND Gates | SN 15961 | SN 15861 | J | N U |
| Triple 3-Input NAND Gates | SN 15963 | SN 15863 | J | N U |
| Dual 5-Input NAND Gates | SN 151901 | SN 151801 | J | N U |
| Expandable 8-Input NAND Gates | SN 151903 | SN 151803 | J | N U |
| 10-Input NAND Gates | SN 151905 | SN 151805 | J | N U |
| Quadruple 2-Input AND Gates | SN 151907 | SN 151807 | J | N U |
| Quadruple 2-Input OR Gates | SN 151909 | SN 151809 | J | N U |
| Quadruple 2-Input NOR Gates | SN 151911 | SN 151811 | J | N U |
| POWER/BUFFER GATES | | | | |
| Expandable Dual 4-Input NAND Buffer Gates | SN 15932 | SN 15832 | J | N U |
| Expandable Dual 4-Input NAND Power Gates | SN 15944 | SN 15844 | J | N U |
| Quadruple 2-Input NAND Buffer Gates | SN 15957 | SN 15857 | J | N U |
| Quadruple 2-Input NAND Power Gates | SN 15958 | SN 15858 | J | N U |
| HEX INVERTERS | | | | |
| 6-kΩ Pull-Up Resistors | SN 15934 | SN 15834 | J | N U |
| Expandable (Open-Base) or Translator Inputs | SN 15935 | SN 15835 | J | N U |
| 6-kΩ Pull-Up Resistors | SN 15936 | SN 15836 | J | N U |
| 2-kΩ Pull-Up Resistors | SN 15937 | SN 15837 | J | N U |
| Open-Collector Outputs | SN 15938 | SN 15838 | J | N U |
| EXPANDERS | | | | |
| Dual 4-Input Expanders | SN 15933 | SN 15833 | J | N U |
| FLIP-FLOPS | | | | |
| Gated J-K/R-S (6-kΩ Pull-Up Resistors) | SN 15931 | SN 15831 | J | N U |
| Gated J-K/R-S (6-kΩ Pull-Up Resistors) | SN 15945 | SN 15845 | J | N U |
| Gated J-K/R-S (2-kΩ Pull-Up Resistors) | SN 15948 | SN 15848 | J | N U |
| Pulse-Triggered Binary (Active Pull-Up) | SN 15950 | SN 15850 | J | N U |
| Dual J-K, Individual Clocks and Presets (6-kΩ Pull-Up Resistors) | SN 159093 | SN 158093 | J | N U |
| Dual J-K, Individual Clocks and Presets (2-kΩ Pull-Up Resistors) | SN 159094 | SN 158094 | J | N U |
| Dual J-K, Common Clocks and Clears (2-kΩ Pull-Up Resistors) | SN 159097 | SN 158097 | J | N U |
| Dual J-K, Common Clocks and Clears (6-kΩ Pull-Up Resistors) | SN 159099 | SN 158099 | J | N U |
| MONOSTABLE MULTIVIBRATORS | | | | |
| Gated, Negative-Edge-Triggered | SN 15951 | SN 15851 | J | N U |

* For outline drawings of all packages, see Section 1.


—SEE ORDERING INSTRUCTIONS PAGE 1-1—

TEXAS INSTRUMENTS
INCORPORATED
POST OFFICE BOX 5012 • DALLAS, TEXAS 75222


11

SERIES 15830, SERIES 15930 DTL INTEGRATED CIRCUITS


SN15830, SN15832,
SN15844, SN15861,
SN15930, SN15932,
SN15944, SN15961




SN15831, SN15845,
SN15848, SN15931,
SN15945, SN15948,
(See Truth Tables 1 and 2)




SN15833, SN15933




SN15834, SN15934




SN15835, SN15836,
SN15837, SN15838,
SN15935, SN15936,
SN15937, SN15938



SN15846, SN15849,
SN15946, SN15949




SN15850, SN15950
(See Truth Tables 3 and 4)



Each RC is a 1-kΩ resistor to VCC.

SN15851, SN15951
(See Notes A, B, and C)



TRUTH TABLE 1
R-S MODE

| t_n | | | | t_{n+1} | |
|-------|----|----|----|---------------|---------------|
| S1 | S2 | C1 | C2 | Q | \bar{Q} |
| L | X | L | X | Q_n | \bar{Q}_n |
| L | X | X | L | Q_n | \bar{Q}_n |
| X | L | L | X | Q_n | \bar{Q}_n |
| X | L | X | L | Q_n | \bar{Q}_n |
| L | X | H | H | L | L |
| X | L | H | H | L | L |
| H | H | L | X | H | H |
| H | H | X | L | H | H |
| H | H | H | H | Indeterminate | Indeterminate |

TRUTH TABLE 2
J-K MODE

| t_n | | t_{n+1} | |
|-------|----|-------------|-------------|
| S1 | C1 | Q | \bar{Q} |
| L | L | Q_n | \bar{Q}_n |
| L | H | L | L |
| H | L | H | H |
| H | H | \bar{Q}_n | Q_n |

TRUTH TABLE 3
SYNCHRONOUS

| t_n | | | | t_{n+1} | |
|-------------|---|-----|-----|---------------|---------------|
| PULSE INPUT | | | | OUTPUT | |
| S | C | PT1 | PT2 | Q | \bar{Q} |
| H | X | X | H | Q_n | \bar{Q}_n |
| X | H | H | X | Q_n | \bar{Q}_n |
| L | H | L | X | H | L |
| L | X | L | H | H | L |
| H | L | X | L | L | H |
| X | L | H | L | L | H |
| L | L | L | L | Indeterminate | Indeterminate |

TRUTH TABLE 4
ASYNCHRONOUS

| DIRECT INPUT | | OUTPUT | |
|--------------|----|--------|-------------|
| SD | CD | Q | \bar{Q} |
| H | H | Q_n | \bar{Q}_n |
| L | H | L | H |
| H | L | H | L |
| L | L | H | H |


- NOTES:
- t_n = bit time before clock pulse.
 - t_{n+1} = bit time after clock pulse.
 - H = high, L = low, X = irrelevant.
 - For operation in the J-K mode connect S2 to Q and C2 to \bar{Q} .

- NOTES:
- Logical levels shown for pulse inputs PT1 and PT2 indicate that a transition to that level has just occurred.
 - Truth tables reflect individual conditions at the input. Either direct input may be used to inhibit its corresponding pulse input.


- NOTES:
- External timing resistor may be connected between pins 14 and 10 to control pulse width.
 - External timing capacitor may be connected between pins 10 and 11 to control pulse width.
 - Input sensitivity can be decreased by adding a capacitor from pin 5 to ground.

SERIES 15830, SERIES 15930 DTL INTEGRATED CIRCUITS


SN15857, SN15858,
SN15957, SN15958




SN15862, SN15863,
SN15962, SN15963




SN151800, SN151801,
SN151900, SN151901




SN151802, SN151803,
SN151902, SN151903




SN151804, SN151805,
SN151904, SN151905




SN151806, SN151807,
SN151906, SN151907




SN151808, SN151809,
SN151908, SN151909




SN151810, SN151811,
SN151910, SN151911




SN151812,
SN151912



SN158093, SN158094,
SN159093, SN159094
(See Truth Table 5)



SN158097, SN158099,
SN159097, SN159099
(See Truth Table 5)



TRUTH TABLE 5

| | t_n | t_{n+1} | |
|---|-------|-----------|-------------|
| | J | K | Q |
| L | L | L | Q_n |
| L | H | L | L |
| H | L | L | H |
| H | H | H | \bar{Q}_n |

**SERIES 15830, SERIES 15930
DTL INTEGRATED CIRCUITS**

**SERIES 15930 GATES, EXPANDER, AND ONE-SHOT
electrical and switching characteristics (unless otherwise noted, $V_{CC} = 5\text{ V}$)**

| PARAMETER | CONDITIONS | T_A (°C) | SN15830 | | SN15937 | | SN15837 | | SN15944 | | SN15951 | | SN151907 | | SN151908 | | SN151909 | | SN151910 | | SN151911 | | SN151912 | | UNIT |
|-----------|-----------------------|------------|---------|------|---------|-------|---------|-------|---------|--------|---------|-------|----------|-------|----------|-------|----------|-------|----------|-------|----------|-------|----------|-------|---------------|
| | | | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | |
| V_{OL} | $I_O = I_{OL}$ MIN | -55 and 75 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | V |
| | | | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | |
| V_{OH} | $I_O = I_{OH}$ MIN | -55 | 2.5 | 2.5 | 3.8 | 3.8 | 3.8 | 3.8 | 6(1,2) | 6(1,2) | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | V |
| | | 75 | 2.6 | 2.6 | 2.6 | 2.6 | 2.6 | 2.6 | 6(1,2) | 6(1,2) | 2.6 | 2.6 | 2.6 | 2.6 | 2.6 | 2.6 | 2.6 | 2.6 | 2.6 | 2.6 | 2.6 | 2.6 | 2.6 | 2.6 | |
| | | 125 | 2.5 | 2.5 | 3.7 | 3.7 | 3.7 | 3.7 | | | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | |
| V_{IL} | | -55 | 1.4 | 1.4 | 2.38 | 2.38 | 2.38 | 2.38 | 1.4 | 1.4 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.4 | V |
| | | 75 | 1.1 | 1.1 | 1.92 | 1.92 | 1.92 | 1.92 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | |
| | | 125 | 0.8 | 0.8 | 1.45 | 1.45 | 1.45 | 1.45 | 0.8 | 0.8 | 0.8 | 0.8 | 0.8 | 0.8 | 0.8 | 0.8 | 0.8 | 0.8 | 0.8 | 0.8 | 0.8 | 0.8 | 0.8 | 0.8 | |
| V_{IH} | | -55 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | V |
| | | 75 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | |
| | | 125 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | 1.7 | |
| I_{OL} | $V_O = V_{OL}$ MAX | -55 | 11.4 | 34 | 11.4 | 11.4 | 11.4 | 11.4 | 36 | 36 | 15 | 11.4 | 10.4 | 11.4 | 11.4 | 10.4 | 11.4 | 10.4 | 11.4 | 11.4 | 10.4 | 11.4 | 11.4 | 11.4 | mA |
| | | 75 | 12 | 36 | 12 | 12 | 12 | 12 | 40 | 40 | 15 | 15 | 12 | 11 | 12 | 11 | 12 | 11 | 12 | 11 | 12 | 11 | 12 | 12 | |
| | | 125 | 10.8 | 32 | 10.8 | 10.8 | 10.8 | 10.8 | 36 | 36 | 14 | 10.8 | 9.8 | 10.8 | 10.8 | 9.8 | 10.8 | 9.8 | 10.8 | 10.8 | 9.8 | 10.8 | 10.8 | 10.8 | |
| I_{OH} | $V_O = V_{OH}$ MIN | -55 | -0.12 | -7 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | -0.18 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | mA |
| | | 75 | -0.12 | -7.5 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | -0.18 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | |
| | | 125 | -0.12 | -3 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | -0.18 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | -0.5 | -0.12 | |
| I_{OS} | $V_O = 0\text{ V}$ | -55 and 75 | -1.34 | -18 | -1.34 | -1.34 | -1.34 | -1.34 | -2.113 | -3.7 | -1.34 | -1.34 | -4 | -1.34 | -4 | -1.34 | -4 | -1.34 | -4 | -1.34 | -4 | -1.34 | -4 | -1.34 | mA |
| | | 125 | -1.3 | -18 | -1.3 | -1.3 | -1.3 | -1.3 | -3.28 | -3.28 | -1.3 | -1.3 | -3.9 | -1.3 | -3.9 | -1.3 | -3.9 | -1.3 | -3.9 | -1.3 | -3.9 | -1.3 | -3.9 | -1.3 | |
| I_{IL} | $V_I = 0\text{ V}$ | -55 and 75 | -1.6 | -16 | -1.6 | -1.6 | -1.6 | -1.6 | -1.6 | -1.6 | -1.6 | -1.6 | -3.1 | -1.6 | -3.1 | -1.6 | -3.1 | -1.6 | -3.1 | -1.6 | -3.1 | -1.6 | -3.1 | -1.6 | mA |
| | | 125 | -1.5 | -15 | -1.5 | -1.5 | -1.5 | -1.5 | -1.5 | -1.5 | -1.5 | -1.5 | -3 | -1.5 | -3 | -1.5 | -3 | -1.5 | -3 | -1.5 | -3 | -1.5 | -3 | -1.5 | |
| I_{IH} | $V_I = 4\text{ V}$ | -55 and 75 | 2 | 5 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | μA |
| | | 125 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | |
| I_F | $I_F = 2\text{ mA}$ | -55 | 0.85 | 0.82 | 0.85 | 0.82 | 0.85 | 0.82 | 0.85 | 0.82 | 0.85 | 0.82 | 0.85 | 0.82 | 0.85 | 0.82 | 0.85 | 0.82 | 0.85 | 0.82 | 0.85 | 0.82 | 0.85 | 0.82 | V |
| | | 75 | 0.7 | 0.82 | 0.7 | 0.82 | 0.7 | 0.82 | 0.7 | 0.82 | 0.7 | 0.82 | 0.7 | 0.82 | 0.7 | 0.82 | 0.7 | 0.82 | 0.7 | 0.82 | 0.7 | 0.82 | 0.7 | 0.82 | |
| I_{CCL} | AVG PER GATE | 75 | 3.25 | 13.3 | 3.25 | 3.25 | 3.25 | 3.25 | 3.25 | 3.25 | 10 | 4.88 | 7.25 | 6.25 | 6.25 | 8.38 | 5 | 6.8 | 5 | 6.8 | 5 | 6.8 | 5 | 6.8 | mA |
| I_{CCH} | AVG PER GATE | 25 | 2.75 | 3 | 2.75 | 2.75 | 2.75 | 2.75 | 2.75 | 3 | 20 | 8.5 | 8.5 | 12.5 | 12.5 | 12.5 | 4.87 | 4.87 | 11.26 | 4.87 | 4.87 | 11.26 | 4.87 | 11.26 | mA |
| I_{PHL} | $V_{CC} = 5\text{ V}$ | 25 | 10 | 30 | 15 | 40 | 10 | 30 | 10 | 30 | 10 | 35 | 5 | 50 | 15 | 65 | 15 | 65 | 15 | 65 | 15 | 65 | 15 | 65 | ns |
| | | 75 | 10 | 30 | 15 | 40 | 10 | 30 | 10 | 30 | 10 | 35 | 5 | 50 | 15 | 65 | 15 | 65 | 15 | 65 | 15 | 65 | 15 | 65 | |
| | | 125 | 25 | 80 | 25 | 80 | 25 | 80 | 25 | 80 | 15 | 60 | 25 | 80 | 15 | 60 | 25 | 80 | 15 | 60 | 25 | 80 | 15 | 60 | |

- (1) 25°C only.
 - (2) For the SN15938, SN15944, and SN15958, V_{OH} is measured at 5 mA.
 - (3) $V_I = 0.98\text{ V}$ at $T_A = -55^\circ\text{C}$, 0.82 V at $T_A = 25^\circ\text{C}$, and 0.65 V at $T_A = 125^\circ\text{C}$.
 - (4) For the SN15951, total quiescent values of I_{CC} are given for $V_{CC} = 5\text{ V}$ and $V_{CC} = 8\text{ V}$.
- NOTE A: This monostable multivibrator is triggered with a negative-going transition ≥ 1 volt having a fall time ≤ 25 ns/volt.

**TEXAS INSTRUMENTS
INCORPORATED**
POST OFFICE BOX 5012 • DALLAS, TEXAS 75222

**SERIES 15830, SERIES 15930
DTL INTEGRATED CIRCUITS**

SERIES 15830 DTL FLIP-FLOPS

electrical and switching characteristics (unless otherwise noted, $V_{CC} = 5$)

| PARAMETER | CONDITIONS | TA (°C) | SN15831 | | SN15845 | | SN15848 | | SN15850 | | SN158093 | | SN158097 | | SN158099 | | UNIT | | |
|-----------|----------------------|---------------|---------|-------|---------|-------|---------|------|---------|-----|----------|-----|----------|-----|----------|-----|-------|-----|-----|
| | | | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | | MIN | MAX |
| VOL | IO = IOL MIN | 0 and 25 | 0.45 | | 0.45 | | 0.45 | | 0.45 | | 0.45 | | 0.45 | | 0.45 | | 0.45 | V | |
| | | 75 | 0.5 | | 0.5 | | 0.5 | | 0.5 | | 0.5 | | 0.5 | | 0.5 | | 0.5 | V | |
| VOH | IO = IOH MIN | 0 and 25 | 2.6 | | 2.6 | | 3.8 | | 2.6 | | 3.8 | | 3.8 | | 3.8 | | 2.6 | V | |
| | | 75 | 2.5 | | 2.5 | | 3.7 | | 2.5 | | 3.7 | | 3.7 | | 3.7 | | 2.5 | V | |
| VIL | | 0 | 1.2 | | 1.2 | | 1.2 | | 1.2 | | 1.2 | | 1.2 | | 1.2 | | 1.2 | V | |
| | | 25 | 1.1 | | 1.1 | | 1.1 | | 1.1 | | 1.1 | | 1.1 | | 1.1 | | 1.1 | V | |
| VIH | | 0 | 2 | | 2 | | 2 | | 2 | | 2 | | 2 | | 2 | | 2 | V | |
| | | 25 | 1.9 | | 1.9 | | 1.9 | | 1.9 | | 1.9 | | 1.9 | | 1.9 | | 1.9 | V | |
| IOL | VO = VOL MAX | 0 and 25 | 10.5 | | 16.8 | | 15.4 | | 12 | | 16.8 | | 15.4 | | 15.4 | | 16.8 | mA | |
| | | 75 | 10.2 | | 16 | | 14.6 | | 11.4 | | 16 | | 14.6 | | 14.6 | | 16 | mA | |
| IOH | VO = VOH MIN | 0, 25, and 75 | -0.12 | | -0.12 | | -0.12 | | -1.5 | | -0.12 | | -0.12 | | -0.12 | | -0.12 | mA | |
| | | 0 | -0.59 | -1.41 | -1.77 | -4.2 | -13.7 | -29 | | | | | | | | | | mA | |
| IOS | VO = 0 V | 25 | | | -0.59 | -1.41 | -1.77 | -4.2 | -13.7 | -29 | | | | | | | | mA | |
| | | 75 | | | -0.55 | -1.38 | -1.6 | -4 | -12.6 | -28 | | | | | | | | mA | |
| IIL | VI = VOL MAX | 0 and 25 | -1.05 | | -0.95 | | -0.95 | | -2.1 | | -0.95 | | -0.95 | | -0.95 | | -0.95 | mA | |
| | | 75 | -1 | | -0.9 | | -0.9 | | -2 | | -0.9 | | -0.9 | | -0.9 | | -0.9 | mA | |
| | | 0 and 25 | -2.8 | | -2.8 | | -2.24 | | | | -2.8 | | -2.8 | | -2.8 | | -5.6 | mA | |
| | | 75 | -2.67 | | -2.67 | | -2.13 | | | | -2.67 | | -2.67 | | -2.67 | | -5.34 | mA | |
| | | 0 and 25 | -0.95 | | -2.1 | | -2.1 | | -1.6 | | -2.8 | | -2.8 | | -2.8 | (1) | -2.8 | mA | |
| | | 75 | -0.9 | | -2 | | -2 | | -1.52 | | -2.67 | | -2.67 | | -2.67 | | -2.67 | mA | |
| IIH | VI = 4 V | 0 and 25 | 5 | | 5 | | 5 | | 5 | | 5 | | 5 | | 5 | | 5 | μA | |
| | | 75 | 10 | | 10 | | 10 | | 10 | | 10 | | 10 | | 10 | | 10 | μA | |
| | | 0 and 25 | 30 | | 20 | | 20 | | 20 | | 20 | | 20 | | 20 | | 40 | μA | |
| | | 75 | 40 | | 30 | | 30 | | 30 | | 30 | | 30 | | 30 | | 60 | μA | |
| | | 0 and 25 | 5 | | 5 | | 5 | | 5 | | 5 | | 5 | | 5 | (1) | 5 | μA | |
| | | 75 | 10 | | 10 | | 10 | | 10 | | 10 | | 10 | | 10 | | 10 | μA | |
| ICC | VCC = 8 V | 25 | 14 | | 16 | | 17.5 | | 9.3 | | 32 | | 35 | | 35 | | 32 | mA | |
| | | 75 | 18 | | 18.5 | | 22.5 | | 19.6 | | 37 | | 45 | | 45 | | 37 | mA | |
| tPHL | FROM CLOCK TO OUTPUT | 25 | 36 | 75 | 15 | 75 | 15 | 65 | 5 | 32 | 15 | 75 | 15 | 65 | 15 | 75 | 75 | ns | |
| | | 75 | 35 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | ns |
| tPLH | FROM CLOCK TO OUTPUT | 25 | 35 | 75 | 25 | 75 | 25 | 75 | 5 | 25 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | ns |
| | | 75 | 35 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | ns |

(1) Double the limit for the common clear input.

**SERIES 15830, SERIES 15930
DTL INTEGRATED CIRCUITS**

SERIES 15930 DTL FLIP-FLOPS

electrical and switching characteristics (unless otherwise noted, VCC = 5)

| PARAMETER | CONDITIONS | TA (°C) | SN15931 MIN | SN15945 MAX | SN15948 MIN | SN15948 MAX | SN15950 MIN | SN15950 MAX | SN15903 MIN | SN15903 MAX | SN15904 MIN | SN15904 MAX | SN15907 MIN | SN15907 MAX | SN15909 MIN | SN15909 MAX | UNIT | |
|-----------|-----------------------|------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|------|----|
| VOL | IO = IOL MIN | -55 and 25 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 | V | |
| | | 125 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | 0.45 | V | |
| VOH | IO = IOH MIN | -55 | 2.5 | 2.6 | 3.8 | 3.8 | 3.8 | 3.8 | 2.5 | 2.6 | 3.8 | 3.8 | 3.8 | 2.6 | 2.5 | 2.5 | V | |
| | | 125 | 2.5 | 2.5 | 3.7 | 3.7 | 3.7 | 3.7 | 2.5 | 2.5 | 3.7 | 3.7 | 3.7 | 2.5 | 2.5 | 2.5 | V | |
| VIL | | -55 | 1.1 | 1.1 | 1.4 | 1.4 | 1.4 | 1.4 | 1.4 | 1.1 | 1.1 | 1.1 | 1.1 | 1.4 | 1.1 | 1.1 | V | |
| | | 125 | 0.95 | 0.8 | 1.1 | 1.1 | 1.1 | 1.1 | 1.1 | 0.8 | 0.8 | 0.8 | 0.8 | 1.1 | 0.8 | 0.8 | V | |
| VIH | | -55 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | 2.1 | V | |
| | | 125 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | V | |
| IOL | VO = VOL MAX | -55 | 10 | 14.6 | 13 | 13 | 11.4 | 14.6 | 13 | 15.2 | 13 | 13.6 | 13.6 | 15.2 | 14.6 | 14.6 | mA | |
| | | 125 | 9.5 | 13.8 | 12.3 | 12.3 | 10.8 | 13.8 | 12.3 | 13.8 | 12.3 | 12.3 | 12.3 | 13.8 | 13.8 | 13.8 | mA | |
| IOH | VO = VOH MIN | -55 | -0.12 | -0.12 | -0.12 | -0.12 | -1.5 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | mA | |
| | | 125 | -0.12 | -0.12 | -0.12 | -0.12 | -1.5 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | -0.12 | mA | |
| IOS | VO = 0 V | -55 and 25 | -0.7 | -1.33 | -2.1 | -3.96 | -15.7 | -27 | -0.7(1) | -2.4(1) | -2.1(1) | -5(1) | -2.1(1) | -5(1) | -0.7(1) | -2.4(1) | mA | |
| | | 125 | -0.62 | -1.3 | -1.86 | -3.54 | -14.6 | -26 | -0.7 | -2.4 | -2.1 | -5 | -2.1 | -5 | -0.7 | -2.4 | mA | |
| IIL | VI = 0 V | -55 and 25 | -1.07 | -1.07 | -1.07 | -1.07 | -2.4 | -1.07 | -1.07 | -1.07 | -1.07 | -1.07 | -1.07 | -1.07 | -1.07 | -1.07 | mA | |
| | | 125 | -1 | -1 | -1 | -1 | -2.25 | -1 | -1 | -1 | -1 | -1 | -1 | -1 | -1 | -1 | mA | |
| IIL | CLOCK INPUT | -55 and 25 | -3.4 | -3.2 | -2.56 | -2.56 | | | -3.2 | -3.2 | -3.2 | -3.2 | -6.4 | -6.4 | -6.4 | -6.4 | mA | |
| | | 125 | -3 | -2.8 | -2.2 | -2.2 | | | -3 | -3 | -3 | -3 | -6 | -6 | -6 | -6 | mA | |
| IIL | PRESET or CLEAR INPUT | -55 | -1.2 | -2.4 | -2.4 | -2.4 | -1.82 | -2.4 | -3.2 | -3.2 | -3.2 | -3.2 | (?) | -3.2 | (?) | -3.2 | mA | |
| | | 125 | -1.1 | -2.1 | -2.1 | -2.1 | -1.62 | -2.1 | -3.0 | -3.0 | -3.0 | -3.0 | -3.0 | -3.0 | -3.0 | -3.0 | mA | |
| IIH | VI = 4 V | -55 and 25 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | μA | |
| | | 125 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | μA | |
| IIL | CLOCK INPUT | -55 and 25 | 20 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 20 | 20 | 20 | μA | |
| | | 125 | 30 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 40 | 40 | 40 | μA | |
| IIL | PRESET or CLEAR INPUT | -55 and 25 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | (?) | (?) | (?) | μA | |
| | | 125 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | μA | |
| ICC | VCC = 8 V | 25 | 11 | 14 | 16.2 | 8.7 | 28 | 32 | 28 | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 28 | mA |
| | | 125 | 14.5 | 17 | 21.6 | 18.4 | 34 | 42 | 34 | 42 | 42 | 42 | 42 | 42 | 42 | 42 | 34 | mA |
| IPLH | FROM CLOCK TO OUTPUT | 25 | 35 | 75 | 15 | 75 | 15 | 65 | 5 | 32 | 15 | 75 | 15 | 65 | 15 | 65 | 75 | ns |
| | | 125 | 35 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | ns |
| IPLH | FROM CLOCK TO OUTPUT | 25 | 35 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 75 | ns |
| | | 125 | 35 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | 75 | 25 | ns |

(1) 25°C only.
(2) Double the limit shown for common clear inputs.

PRINTED IN U.S.A.
TI cannot assume any responsibility for any circuits shown or represent that they are free from patent infringement.

TEXAS INSTRUMENTS
INCORPORATED

POST OFFICE BOX 5012 • DALLAS, TEXAS 75222