Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Jameco Part Number 839762

National Semiconductor

February 2005

LM185-2.5/LM285-2.5/LM385-2.5 Micropower Voltage Reference Diode

General Description

The LM185-2.5/LM285-2.5/LM385-2.5 are micropower 2-terminal band-gap voltage regulator diodes. Operating over a 20 µA to 20 mA current range, they feature exceptionally low dynamic impedance and good temperature stability. On-chip trimming is used to provide tight voltage tolerance. Since the LM-185-2.5 band-gap reference uses only transistors and resistors, low noise and good long term stability result.

Careful design of the LM185-2.5 has made the device exceptionally tolerant of capacitive loading, making it easy to use in almost any reference application. The wide dynamic operating range allows its use with widely varying supplies with excellent regulation.

The extremely low power drain of the LM185-2.5 makes it useful for micropower circuitry. This voltage reference can be used to make portable meters, regulators or general purpose analog circuitry with battery life approaching shelf life. Further, the wide operating current allows it to replace older references with a tighter tolerance part. For applications requiring 1.2V see LM185-1.2.


The LM185-2.5 is rated for operation over a –55˚C to 125˚C temperature range while the LM285-2.5 is rated –40˚C to 85˚C and the LM385-2.5 0˚C to 70˚C. The LM185-2.5/LM285-2.5 are available in a hermetic TO-46 package and the LM285-2.5/LM385-2.5 are also available in a low-cost TO-92 molded package, as well as S.O. and SOT-23. The LM185-2.5 is also available in a hermetic leadless chip carrier package.

Features

- ±20 mV (±0.8%) max. initial tolerance (A grade)
- Operating current of 20 µA to 20 mA
- 0.6Ω dynamic impedance (A grade)
- Low temperature coefficient
- Low voltage reference — 2.5V
- 1.2V device and adjustable device also available — LM185-1.2 series and LM185 series, respectively

Connection Diagrams


TO-92
Plastic Package



00551908

Bottom View
Order Number LM285Z-2.5,
LM285BXZ-2.5, LM285BYZ-2.5
LM385Z-2.5, LM385AXZ-2.5
LM385AYZ-2.5, LM385BZ-2.5,
LM385BXZ-2.5 or LM385BYZ-2.5
See NS Package Number Z03A


SO Package



00551911

Order Number LM285M-2.5,
LM285BXM-2.5, LM285BYM-2.5
LM385M-2.5, LM385BM-2.5
LM385BXM-2.5 or LM385BYM-2.5
See NS Package Number M08A

SOT-23



00551929


* Pin 3 is attached to the Die Attach Pad (DAP) and should be connected to Pin 2 or left floating.

Order Number LM385M3-2.5
See NS Package Number MA03B

© 2005 National Semiconductor Corporation

Connection Diagrams (Continued)


LCC
Leadless Chip Carrier



00551914

Order Number LM185E-2.5/883
See NS Package Number E20A

TO-46
Metal Can Package



00551913

Bottom View
Order Number LM185H-2.5,
LM185H-2.5/883, LM185BXH-2.5,
LM185BXH-2.5/883, LM185BYH-2.5,
LM185BYH2.5/883, LM285H-2.5,
or LM285BYH-2.5
See NS Package Number H02A

Absolute Maximum Ratings (Notes 1, 2)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/ Distributors for availability and specifications.

Reverse Current	30 mA
Forward Current	10 mA
Operating Temperature Range (Note 3)	
LM185-2.5	−55˚C to + 125˚C
LM285-2.5	−40˚C to + 85˚C
LM385-2.5	0˚C to 70˚C
Storage Temperature	−55˚C to + 150˚C
Soldering Information	
TO-92 Package (10 sec.)	260˚C
TO-46 Package (10 sec.)	300˚C
SO and SOT Package	
Vapor Phase (60 sec.)	215˚C
Infrared (15 sec.)	220˚C

See AN-450 “Surface Mounting Methods and Their Effect on Product Reliability” for other methods of soldering surface mount devices.

Electrical Characteristics

(Note 4)

Parameter	Conditions	Typ	LM385A-2.5 LM385AX-2.5 LM385AY-2.5		Units (Limits)
			Tested Limit (Note 5)	Design Limit (Note 6)	
Reverse Breakdown Voltage	I_R = 100 µA	2.500	2.480		V(Min)
			2.520		V(Max)
		2.500		**2.470**	V(Min)
				2.530	V(Max)
Minimum Operating Current		12	18	**20**	µA (Max)
Reverse Breakdown Voltage Change with Current	$I_{MIN} \le I_R \le$ 1mA		1	**1.5**	mV (Max)
	1 mA ≤ I_R ≤ 20 mA		10	**20**	mV (Max)
Reverse Dynamic Impedance	I_R = 100 µA, f = 20 Hz	0.2		0.6	Ω
				1.5	
Wideband Noise (rms)	I_R = 100 µA 10 Hz ≤ f ≤ 10 kHz	120			µV
Long Term Stability	I_R = 100 µA, T = 1000 Hr, T_A = 25˚C ±0.1˚C	20			ppm
Average Temperature Coefficient (Note 7)	$I_{MIN} \le I_R \le$ 20 mA				
	X Suffix		**30**		ppm/˚C
	Y Suffix		**50**		(Max)
	All Others			**150**	

Electrical Characteristics

Parameter	Conditions	Typ	LM185-2.5 LM185BX-2.5 LM185BY-2.5 LM285-2.5 LM285BX-2.5 LM285BY-2.5		LM385B-2.5 LM385BX-2.5 LM385BY-2.5		LM385-2.5		Units (Limit)
			Tested Limit (Note 5) (Note 8)	Design Limit (Note 6)	Tested Limit (Note 5)	Design Limit (Note 6)	Tested Limit (Note 5)	Design Limit (Note 6)	
Reverse Breakdown Voltage	T_A = 25˚C, 20 µA ≤ I_R ≤ 20 mA	2.5	2.462 2.538		2.462 2.538		2.425 2.575		V(Min) V(Max)
Minimum Operating Current		13	20	**30**	20	**30**	20	**30**	µA (Max)
	LM385M3-2.5						15	**20**	
Reverse Breakdown Voltage Change with Current	20 µA ≤ I_R ≤ 1 mA		1	**1.5**	2.0	**2.5**	2.0	**2.5**	mV (Max)
	1 mA ≤ I_R ≤ 20 mA		10	**20**	20	**25**	20	**25**	mV (Max)
Reverse Dynamic Impedance	I_R = 100 µA, f = 20 Hz	1							Ω
Wideband Noise (rms)	I_R = 100 µA, 10 Hz ≤ f ≤ 10 kHz	120							µV
Long Term Stability	I_R = 100 µA, T = 1000 Hr, T_A = 25˚C ±0.1˚C	20							ppm
Average Temperature Coefficient (Note 7)	I_R = 100 µA								
	X Suffix		**30**		**30**				ppm/˚C
	Y Suffix		**50**		**50**				ppm/˚C
	All Others			**150**		**150**		**150**	ppm/˚C (Max)

Note 1: Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is intended to be functional, but do not guarantee specific performance limits. For guaranteed specifications and test conditions, see the Electrical Characteristics. The guaranteed specifications apply only for the test conditions listed.

Note 2: Refer to RETS185H-2.5 for military specifications.

Note 3: For elevated temperature operation, $T_{J\ MAX}$ is:

LM185 150˚C
LM285 125˚C
LM385 100˚C

Thermal Resistance	TO-92	TO-46	SO-8	SOT-23
θ_{ja} (Junction to Ambient)	180˚C/W (0.4" Leads) 170˚C/W (0.125" Leads)	440˚C/W	165˚C/W	283˚C/W
θ_{jc} (Junction to Case)	N/A	80˚C/W	N/A	N/A

Note 4: Parameters identified with boldface type apply at temperature extremes. All other numbers apply at $T_A = T_J = 25^\circ C$.

Note 5: Guaranteed and 100% production tested.


Note 6: Guaranteed, but not 100% production tested. These limits are not used to calculate average outgoing quality levels.

Note 7: The average temperature coefficient is defined as the maximum deviation of reference voltage at all measured temperatures between the operating T_{MAX} and T_{MIN}, divided by $T_{MAX}-T_{MIN}$. The measured temperatures are –55˚C, –40˚C, 0˚C, 25˚C, 70˚C, 85˚C, 125˚C.

Note 8: A military RETS electrical specification available on request.


Typical Performance Characteristics

Reverse Characteristics




00551915

Reverse Characteristics




00551916

Forward Characteristics




00551917

Temperature Drift




00551918

Reverse Dynamic Impedance



00551919


Reverse Dynamic Impedance



00551920


Typical Performance Characteristics (Continued)

Noise Voltage




00551921

Filtered Output Noise



00551922


Response Time



00551923


Applications

Wide Input Range Reference



00551912


Micropower Reference from 9V Battery



00551902

LM385-2.5 Applications

Micropower 5V Reference (Note 9)




00551909

Note 9: $I_Q \simeq 40$ μA

LM385-2.5 Applications (Continued)


Micropower 10V Reference (Note 10)



00551910


Note 10: $I_Q \simeq 30\ \mu A$ standby current

Precision 1 µA to 1 mA Current Sources



00551924

$$*I_{OUT} = \frac{2.5V}{R2}$$




00551925

LM385-2.5 Applications (Continued)

METER THERMOMETERS

0˚C–100˚C Thermomemter




00551926

Calibration

1. Short LM385-2.5, adjust R3 for I_{OUT}=temp at 1μA/˚K
2. Remove short, adjust R2 for correct reading in centigrade

0˚F–50˚F Thermomemter




00551927

Calibration

1. Short LM385-2.5, adjust R3 for I_{OUT}=temp at 1.8 μA/˚K
2. Remove short, adjust R2 for correct reading in ˚F

Micropower Thermocouple Cold Junction Compensator



00551906

Adjustment Procedure


1. Adjust TC ADJ pot until voltage across R1 equals Kelvin temperature multiplied by the thermocouple Seebeck coefficient.
2. Adjust zero ADJ pot until voltage across R2 equals the thermocouple Seebeck coefficient multiplied by 273.2.

Thermocouple Type	Seebeck Co-efficient (μV/˚C)	R1 (Ω)	R2 (Ω)	Voltage Across R1 @25˚C (mV)	Voltage Across R2 (mV)
J	52.3	523	1.24k	15.60	14.32
T	42.8	432	1k	12.77	11.78
K	40.8	412	953Ω	12.17	11.17
S	6.4	63.4	150Ω	1.908	1.766

Typical supply current 50 μA


LM385-2.5 Applications (Continued)

Improving Regulation of Adjstable Regulators



00551907


Schematic Diagram



00551901


Physical Dimensions inches (millimeters)

unless otherwise noted



E20A (Rev F)


Order Number LM185E-2.5/883
NS Package Number E20A



H02A (Rev F)


TO-46 Metal Can Package (H)
Order Number LM185H-2.5, LM185H-2.5/883, LM185BXH-2.5, LM185BXH-2.5/883, LM185BYH-2.5, LM185BYH-2.5/883, LM285H-2.5, or LM285BYH-2.5
NS Package Number H02A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



SOT-23 Package (M3)
Order Number LM385M3-2.5
NS Package Number MA03B

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)




CONTROLLING DIMENSION IS MILLIMETER
VALUES IN [ ] ARE INCHES
DIMENSIONS IN ( ) FOR REFERENCE ONLY

M08A (Rev K)

Small Outline (SO-8) Package (M)
Order Number LM285M-2.5, LM285BXM-2.5, LM285BYM-2.5,
LM385M-2.5, LM385BM-2.5, LM385BXM-2.5 or LM385BYM-2.5
NS Package Number M08A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



TO-92 Plastic Package (Z)
Order Number LM285Z-2.5, LM285BXZ-2.5, LM285BYZ-2.5,
LM385Z-2.5, LM385AXZ-2.5, LM385AYZ-2.5,
LM385BZ-2.5, LM385BXZ-2.5 or LM385BYZ-2.5
NS Package Number Z03A

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.

For the most current product information visit us at www.national.com.

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

BANNED SUBSTANCE COMPLIANCE

National Semiconductor manufactures products and uses packing materials that meet the provisions of the Customer Products Stewardship Specification (CSP-9-111C2) and the Banned Substances and Materials of Interest Specification (CSP-9-111S2) and contain no "Banned Substances" as defined in CSP-9-111S2.

National Semiconductor
Americas Customer
Support Center
Email: new.feedback@nsc.com
Tel: 1-800-272-9959

www.national.com

National Semiconductor
Europe Customer Support Center
Fax: +49 (0) 180-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 69 9508 6208
English Tel: +44 (0) 870 24 0 2171
Français Tel: +33 (0) 1 41 91 8790

National Semiconductor
Asia Pacific Customer
Support Center
Email: ap.support@nsc.com

National Semiconductor
Japan Customer Support Center
Fax: 81-3-5639-7507
Email: jpn.feedback@nsc.com
Tel: 81-3-5639-7560