

JINGHAN SWITCH ELECTRONIC CO.,LTD

Attn: Mr John
 Tel: +86-574-83067530
 Mobile: +86-15867263600

Add: #102 65Building Dongying Xincun Ningbo City Zhejiang Province China
 Fax: +86-574-87972399
 E-mail: sales@jhswitch.com Website: <http://www.jhswitch.com>

JINGHAN ROCKER SWITCH KCD1-116B Series Datasheet



项目 Item	参数 Parameter
额定电流、电压 Rated voltage Rated current	6A 250V AC 10A 125V AC
绝缘电阻 Insulated resistance	≥ 100M Ω
接触电阻 Contact resistance	≤ 50m Ω
介电强度(极间) Dielectric strength	1500VAC/5S
电器寿命 Endurance	≥ 10000 Cycles
使用温度 Ambient temperature	T 85

面板开孔 Panel Opening	面板厚度 Panel thickness	X ^{+0.10} ₀	Y ^{+0.10} ₀
	0.6-1.2	19	13
	1.2-2	19.2	
	2-3	19.4	

系列号
Series No

KCD1-116B/2P

KCD1-116B/3P

电路图
Circuit diagram

ON-OFF

ON-ON

端子规格
Terminal

A 4.8 x 0.6

B 2.8 x 0.6

T 1.2 x 0.6

L 1.2 x 0.6

开关标记
Making

1	空白
2	○ —
3	●
4	米 米
5	○
6	LL ON
7	客人要求

颜色代码
Color code

K	
W	
Y	
R	
G	
O	
B	

Electronics specification	Expansion	British Called	American Called	Description	Symbol
SPST	Single pole, single throw	One-way	Two-way	A simple on-off switch. The two terminals are either connected together or disconnected from each other. An example is a light switch.	

JINGHAN SWITCH ELECTRONIC CO.,LTD

Attn: Mr John

Tel: +86-574-83067530




Mobile: +86-15867263600

Add: #102 65Building Dongying Xincun Ningbo City Zhejiang Province China

Fax: +86-574-87972399

E-mail: sales@jhswitch.com

Website: <http://www.jhswitch.com>

SPDT	Single pole, double throw	Two-way	Three-way	A simple changeover switch: C (COM, Common) is connected to L1 or to L2.	
DPST	Double pole, single throw	Double pole	Double pole	Equivalent to two SPST switches controlled by a single mechanism	
DPDT	Double pole, double throw			Equivalent to two SPDT switches controlled by a single mechanism.	

Description of JINGHAN SWITCH KCD1-116B Series Rocker Switch

Types:	ON-OFF (ON)-OFF
Actuator :	Polycarbonate
Base :	Nylon(PA) 66
Contacts :	Silver plated Copper / Silver Alloyed
Movable Arm :	Tin-Plated Copper
Terminals :	Tin-Plated Copper
Ratings :	6A125V 10A250V
Dielectric Strength :	1500V for 1 Min
Insulation Resistance :	≥100MΩ
Contact Resistance :	≤30mΩ
Temperature Range :	-30~85°C
Life :	≥10000times
ROHS:	YES
CE:	YES
TUV:	YES

Between KCD1-116A and KCD1-116B is the panel edge different, please attention.