

# Pump 32-33703LB-01



---

## SPX Johnson Pump 32-33703LB-01 Low Boy Bilge Pump L550 LB-800 GPH, 12V

---

- [Description](#)
- Submersible bilge pump of the Cartridge Series
- Motor can be removed for maintenance or replacement simply without any tools
- Fittings 90° and straight 19mm (3/4") discharge port included
- Capacity at 13,6V straight 50l/min (800 GPH); at 1m (3 ft) head 44l/min (700 GPH)
- Amperage 3A; fuse size 5A
- Dimensions: Length 14,6cm / height 7,2cm / width 8,1 cm

Low Profile pump designed for ease of mounting and removal in tight bilge areas. Perfect for vessels with bilge pumps mounted beneath inboard or I/O engines.

---

Shipping weight: 0,60 Kg

---

LOW BOY - SUBMERSIBLE BILGE PUMP

Part No.	Capacity 3 ft (0.9 m) head 13.6V	Capacity straight 13.6V	Description		
32-33703LB-01	44 l/min - 700 GPH	50 l/min - 800 GPH	LOW BOY BILGE PUMP 750 GPH 12V 3/4"		
Max Length	Width	Height	Wire size	Fuse Size	Amp
146 mm – 5.75"	81 mm – 3.2"	72 mm – 2.82"	16 GA (1.3 mm <sup>2</sup> )	5 A	3 A

Low Profile pump design for ease of mounting and removal in tight bilge areas. Perfect for vessels with bilge pumps mounted beneath inboard or I/O engines. Removable cartridge style.

The 750 GPH Low Boy Bilge pumps has easy-to-install Dura-Port discharge ports to eliminate stress cracking caused by over-tightened hose clamps. The pumps will be delivered including both a straight and a 90° smooth elbow. Use Electro-Magnetic Float Switch (Part No. 34-1900B-12V) only.