












# Cables and Connectors *FDD / HDD cable*

	FDD cable		SATA HDD cable
			
<b>Model name</b>	<b>32200-000017-RS</b>	<b>32200-000058-RS</b>	<b>32000-062800-RS</b>
Cable type	FDD flat cable	FDD flat cable	SATA HDD cable
Connector	34p-34p-34p	34p-34p	SATA 7-pin
Connector type	2.54 mm	2.54 mm-2.0 mm	Lockable
Length	37 cm + 15 cm	35 cm	50 cm

	SATA HDD cable			
				
<b>Model name</b>	<b>32102-000100-200-RS</b>	<b>32000-080700-RS</b>	<b>32801-000201-100-RS</b>	<b>32801-000100-100-RS</b>
Cable type	SATA power cable	SATA + Power cable kit	SATA + Power cable kit	SATA + Power cable
Connector	4-pin model - 2 x SATA 15-pin	SATA 7-pin + 4-pin model	SATA 7-pin + 2-pin wafer 2.0mm	SATA 7-pin + 4-pin wafer 2.54mm
Connector type	SATA Power connector		2-pin PH 2.0	4-pin PH 2.54 mm
Length	15 cm	SATA cable 20 cm Power cable 10 cm	SATA cable 15 cm Power cable 15 cm	SATA cable 20 cm Power cable 20 cm

	IDE HDD cable			
				
<b>Model name</b>	<b>32200-000005-RS</b>	<b>32200-000009-RS</b>	<b>32200-000037-RS</b>	<b>32200-025001-RS</b>
Cable type	IDE HDD flat cable	IDE HDD flat cable	IDE HDD flat cable	IDE HDD flat cable
Connector	40p-40p-40p	44p-44p	44p-44p	44p-40p-40p
Connector type	2.54mm	2.0mm -2.0mm	2.0mm -2.0mm	2.0mm-2.54mm-2.54mm
Length	40 cm + 17 cm	40 cm	25 cm	20 cm + 15 cm

	IDE HDD cable			
				
<b>Model name</b>	<b>32200-000052-RS</b>	<b>32200-008800-RS</b>	<b>CB-HD32-RS</b>	<b>CVT-4044-RS</b>
Cable type	ATA-66 HDD flat cable	ATA-33 HDD flat cable	IDE HDD 40p to 44p	IDE 40p to 44p adapter
Connector	40p-40p-40p	44p-40p-40p	40p-44p	40p-44p
Connector type	2.54mm	2.0mm-2.54mm-2.54mm	2.54mm-2.0mm	2.54mm-2.0mm
Length	30 cm + 15 cm	20 cm + 15 cm	IDE cable: 39 cm Power cable: 20 cm	Power cable: 20 cm

Part numbers listed in the product catalog are for reference purposes. IEI reserves the right to implement substitution parts when the function is not affected.

1

Industrial Computing Solutions

2

Video Capture Solutions

3

Embedded Computing Solutions

4

Industrial Data Collector and Controller

5

Panel Solutions Introduction

6

ORing Network Communication

7

Power Supply/ Peripherals

# Cables and Connectors *Paralle / Serial cable*

	Paralle cable				Serial cable
<b>Model name</b>	<b>19800-000400-100-RS</b>	<b>19800-000142-00-RS</b>	<b>19800-000027-RS</b>	<b>32200-015100-RS</b>	<b>19800-000300-100-RS</b>
Cable type	Parallel port cable	Parallel and serial port cable	Parallel and serial port cable	Parallel port cable	Single com port
Board side	26-pin (2x13) connector (2.54 mm)	26-pin (2x13) connector (2.54 mm) 10-pin (2x5) connector (2.54 mm)	26-pin (2x13) connector (2.0 mm) 10-pin (2x5) connector (2.0 mm)	26-pin (2x13) connector (2.0 mm)	10-pin (2x5) connector (2.0 mm)
Board side pitch	2.54 mm	2.54 mm	2.0 mm	2.0 mm	2.0 mm
Device side	DB25F	DB25F + DE9M	DB25F + DE9M	DB25F	2.0 mm
Bracket	Yes	Yes	Yes	No	YES
Length	24 cm	24 cm	24 cm	28 cm	30cm





	Serial cable					
<b>Model name</b>	<b>19800-000114-RS</b>	<b>19800-000047-RS</b>	<b>19800-000051-RS</b>	<b>19800-000113-RS</b>	<b>19800-000112-RS</b>	<b>32200-000015-RS</b>
Cable type	Single com port	Serial port cable	Serial port cable	Serial port cable	Serial port cable	Serial port cable
Board side	10-pin (2x5) connector (2.54 mm)	10-pin (2x5) connector (2.54 mm)	2 x 10-pin (2x5) connector (2.54 mm)	2 x 10-pin (2x5) connector (2.0 mm)	2 x 10-pin (2x5) connector (2.0 mm)	10-pin (2x5) connector (2.54 mm)
Board side pitch	2.54 mm	2.54 mm	2.54 mm	2.54 mm	2.0 mm	2.54 mm
Device side	DE9M	DE9M	2 x DE9M	2 x DE9M	2 x DE9M	DE9M
Bracket	Yes	Yes	Yes	Yes	Yes	No
Length	50 cm	30 cm	23 cm	40 cm	30 cm	23 cm





	Serial cable					
<b>Model name</b>	<b>32200-000049-RS</b>	<b>32205-001203-100-RS</b>	<b>32100-147900-RS</b>	<b>32200-025401-RS</b>	<b>32200-026800-RS</b>	<b>19800-000058-RS</b>
Cable type	Serial port cable	4 x com port	Serial port cable	Serial port cable	RS-422/485 cable	RS-232 & RS-422/485 cable
Board side	10-pin (2x5) connector (2.0 mm)	40-pin (2x20) connector (2.54 mm)	40-pin (2x20) connector (2.0 mm)	40-pin (2x20) connector (2.0 mm)	16-pin (2x8) connector (2.54 mm)	14-pin (2x7) connector (2.54 mm)
Board side pitch	2.0 mm	2.54 mm	2.0 mm	2.0 mm	2.54 mm	2.54 mm
Device side	DE9M	4 x DE9M	4 x DE9M	4 x DE9M	4 x DE9M	2 x DE9M
Bracket	No	No	No	No	No	Yes
Length	20 cm	40/40/40/40 cm	30 cm	30 cm	12 cm	25.5 cm

	Serial cable				
<b>Model name</b>	<b>19800-000110-RS</b>	<b>32205-000300-100-RS</b>	<b>32200-000061-RS</b>	<b>19800-000063-RS</b>	<b>32200-074800-RS</b>
Cable type	RS-232 & RS-422/485 cable	RS-232 & RS-422/485 cable	RS-232 & RS-422/485 cable	RS-232 & RS-422/485 cable	RS-422/485 cable
Board side	14-pin (2x7) connector (2.0 mm)	14-pin (2x7) connector (2.0 mm)	14-pin (2x7) connector (2.0 mm)	4-pin (1x4) connector (2.54 mm)	4-pin (1x4) connector (2.0 mm)
Board side pitch	2.0 mm	2.0 mm	2.0 mm	2.54 mm	2.0 mm
Device side	2 x DE9M	2 x DE9M	2 x DE9M	DE9M	DE9M
Bracket	Yes	No	No	No	No
Length	25 cm	29 cm	23 cm	40 cm	20 cm






Part numbers listed in the product catalog are for reference purposes. IEI reserves the right to implement substitution parts when the function is not affected.






# Cables and Connectors *USB / 1394 / Y Cable*

	USB cable			
				
<b>Model name</b>	<b>19800-000100-200-RS</b>	<b>CB-USB02-RS</b>	<b>CB-USB02A-RS</b>	<b>32000-044300-RS</b>
Cable type	USB cable	USB cable	USB cable	USB cable
Board side	2 x 4-pin (2x4) connector (2.54mm)	2 x 4-pin (1x4) connector (2.54mm)	1 x 8-pin (2x4) connector (2.0mm)	1 x 8-pin (2x4) connector (2.54mm)
Board side pitch	2.54mm	2.54mm	2.0mm	2.54mm
Device side	4 x USB	2 x USB	2 x USB	2 x USB
Bracket	Yes	Yes	Yes	No
Length	30 cm	30 cm	30 cm	21 cm

	USB cable		1394 cable	
				
<b>Model name</b>	<b>32001-004600-100-RS</b>	<b>32000-070301-RS</b>	<b>CB-IEEE1394-RS</b>	<b>19800-000103-RS</b>
Cable type	USB cable	USB cable	1394 cable	1394 cable
Board side	2 x 5pin connector (2.0mm) for WAFER-8523, WAFER-945GSE3 only	1 x 8-pin (2x4) connector (2.0mm)	2 x 8-pin (1x8) connector (2.0mm)	1 x 8-pin (1x8) connector (2.0mm)
Board side pitch	2.0mm	2.0mm	2.0 mm	2.0 mm
Device side	2 x USB	2 x USB	2 x IEEE1394	1 x IEEE1394
Bracket	No	No	Yes	Yes
Length	40 cm	21 cm	21 cm	25 cm

Pin 1	Pin 2	Pin 3	Pin 4
+12V	GND	TPB-	TPB+
Pin 5	Pin 6	Pin 7	Pin 8
TPA-	TPA+	SHIELD	SHIELD

	Keyboard / Mouse cable				
					
<b>Model name</b>	<b>19800-000066-RS</b>	<b>19800-000075-RS</b>	<b>32006-000300-100-RS</b>	<b>32000-043301-RS</b>	<b>32000-023800-RS</b>
Cable type	Keyboard and mouse cable	Y-Cable	Y-Cable	Y-Cable	Y-Cable
Board side	2 x 5-pin (1x5) connector (2.54mm)	1 x 6-pin (1x6) connector (2.0mm)	1 x male PS/2	1 x 6-pin (1x6) connector (2.54mm)	1 x 6-pin (1x6) connector (2.0mm)
Board side pitch	2.54mm	2.0mm		2.54mm	2.0mm
Device side	2 x female PS/2	2 x female PS/2	2 x female PS/2	2 x female PS/2	2 x female PS/2
Bracket	Yes	Yes	No	No	No
Length	30 cm	22 cm	12cm(KB) + 14(MS)	60 cm	13 cm

	Power cable				
					
<b>Model name</b>	<b>32100-087100-RS</b>	<b>32100-052100-RS</b>	<b>32100-043403-RS</b>	<b>32100-192900-RS</b>	<b>32100-130300-RS</b>
Cable type	12V Power cable	ATX function cable	ATX function cable	12V Power cable	Power cable for PC/104 CPU module
Board side	1 x 4-pin (2x2) connector	1 x 20-pin ATX power connector	1 x 20-pin ATX power connector	1 x 4-pin (2x2) connector	1 x 4-pin(1x4) molex
Device side	2 x 4-pin (1x4) molex	1 x 4-pin(1x4) molex 1 x 3-pin PS_ON connector	PS_ON 2.54mm connector	4-pin 3.5 mm terminal block	3-pin 3.5 mm terminal block
Bracket	No	No	No	No	No
Length	13 cm	30 cm	30 cm	25 cm	10 cm

Part numbers listed in the product catalog are for reference purposes. IEI reserves the right to implement substitution parts when the function is not affected.

1

Industrial Computing Solutions

2

Video Capture Solutions

3

Embedded Computing Solutions

4

Industrial Data Collector and Controller

5

Panel Solutions Introduction




6

ORing Network Communication




7

Power Supply/ Peripherals

# Cables and Connectors *Audio / LAN / VGA / ADAPTER Cable*






	Audio cable		
			
<b>Model name</b>	<b>19800-00043-RS</b>	<b>19800-000800-100-RS</b>	<b>19800-000111-RS</b>
Cable type	Audio and Serial cable	Audio cable	Audio cable
Board side	Audio cable: 4-pin (1x4) connector (2.54mm) Serial cable: 10-pin (2x5) connector (2.0mm)	12-pin (2x6) connector (2.0mm)	10-pin (2x5) connector (2.0mm)
Board side pitch	Audio : 2.54mm Serial cable: 2.0mm	2.0mm	2.0mm
Device side	2 x Audio jacks / 1x DE9M	4 x Audio jacks	3 x Audio jacks
Bracket	Yes	Yes	Yes
Length	30 cm	25 cm	30 cm




	Audio cable		
			
<b>Model name</b>	<b>32000-000147-RS</b>	<b>32000-072100-RS</b>	<b>32000-028800-RS</b>
Cable type	Audio cable	Audio cable	Audio cable
Board side	16-pin (2x8) connector (2.0mm)	10-pin (2x5) connector (2.0mm)	12-pin (2x6) connector (2.54mm)
Board side pitch	2.0mm	2.0mm	2.54mm
Device side	3 x Audio jacks	3 x Audio jacks	4 x Audio jacks
Bracket	No	No	No
Length	25 cm	30 cm	25 cm

	LAN cable	VGA cable	
			
<b>Model name</b>	<b>32000-055702-RS</b>	<b>32000-033800-RS</b>	<b>32000-033804-RS</b>
Cable type	LAN cable	VGA cable	VGA cable
Board side	10-pin (2x5) connector (2.0mm)	10-pin (2x5) connector (2.54mm)	10-pin (2x5) connector (2.0mm)
Board side pitch	2.0mm	2.54mm	2.0mm
Device side	1 x RJ-45	1 x DB15F	1 x DB15F
Bracket	No	No	No
Length	31 cm	30 cm	30 cm

Part numbers listed in the product catalog are for reference purposes. IEL reserves the right to implement substitution parts when the function is not affected.

# Cables and Connectors *Audio / LAN / VGA / ADAPTER / TV / Round Cable*


TV/HDTV-output cable					
					
<b>Model name</b>	<b>19800-000056-RS</b>	<b>32000-132000-RS</b>	<b>32000-132100-RS</b>	<b>32000-083701-RS</b>	<b>32000-083702-RS</b>
<b>Cable type</b>	TV-out cable	HDTV cable	HDTV cable	HDTV cable	HDTV cable
<b>Board side</b>	6-pin (2x3) connector (2.54mm)	1 x Mini-DIN 7-pin connector	1 x Mini-DIN 7-pin connector	6-pin (2x3) connector (2.54mm)	6-pin (2x3) connector (2.0mm)
<b>Board side pitch</b>	2.54mm			2.54mm	2.0mm
<b>Device side</b>	1 x RCA jack 1 x S-video jack	3 x RCA jack 1 x S-video jack	3 x RCA jack	3 x RCA jack	3 x RCA jack
<b>Bracket</b>	Yes	No	No	No	No
<b>Length</b>	25 cm	15cm	15 cm	20 cm	20 cm

Round cable			
			
<b>Model name</b>	<b>32000-026800-RS</b>	<b>32000-026900-RS</b>	<b>32100-047401-RS</b>
<b>Cable type</b>	ATA-66 HDD rounded cable	ATA-66 HDD rounded cable	USB cable
<b>connector</b>	IDE 40p-40p	IDE 40p-40p	1 x 4-pin (1x4) wafer connector (2.0mm)
<b>Board side pitch</b>	2.54mm	2.54mm	2.0mm
<b>Device side</b>	IDE 40-pin	IDE 40-pin	1 x 4-pin (1x4) connector (2.0mm)
<b>Length</b>	75 cm	45 cm	50 cm
<b>Compatible model</b>	RACK-115G, RACK-1151G, RACK-3200G	RACK-115G, RACK-1151G	Fro front accessible USB port

Part numbers listed in the product catalog are for reference purposes. IEI reserves the right to implement substitution parts when the function is not affected.

## Rackmount Slide *Chassis optional Accessories*

SLIDE			
			
<b>Model Name</b>	<b>SLIDE-18</b>	<b>SLIDE-24</b>	<b>EXTENDER-6</b>
<b>Specification</b>	18" rackmount slide	24" rackmount slide	6" extender
<b>Description</b>	For rackmount chassis w/ depth up to 500	For rackmount chassis w/ depth up to 500	For 18" or 24" slider

SLIDE			
			
	20"	24"	26"
<b>Model Name</b>	<b>SLIDE-20NJ-R20</b>	<b>SLIDE-24NJ-R20</b>	<b>SLIDE-26NJ-R20</b>
<b>Specification</b>	20" slide mount	24" slide mount	26" slide mount
<b>Description</b>	20-inch 100 pound loading ball bearing rack-mount slide, RoHS	24-inch 100 pound loading ball bearing rack-mount slide, RoHS	26-inch 100 pound loading ball bearing rack-mount slide, RoHS

1

Industrial Computing Solutions

2

Video Capture Solutions

3

Embedded Computing Solutions

4

Industrial Data Collector and Controller

5

Panel Solutions Introduction

6

ORing Network Communication

7

Power Supply/ Peripherals